



UTILITY PATENT APPLICATION TRANSMITTAL <i>(Only for new nonprovisional applications under 37 CFR § 1.53(h))</i>		Attorney Docket No.	15-4-1034 00
		First Inventor or Application Identifier	Phillip K. KESLIN
		Title	System, Method, and Computer Program Product for Remote Graphics Processing
		Express Mail Label No.	

APPLICATION ELEMENTS <i>See MPEP chapter 600 concerning utility patent application contents</i>	ADDRESS TO: Assistant Commissioner for Patents Box Patent Application Washington, DC 20231
---	---

1. ☒ * Fee Transmittal Form (e.g., PTO/SB/17)
(Submit an original, and a duplicate for fee processing)
2. ☒ Specification [Total Pages 24]
(preferred arrangement set forth below)
- Distinguishing title of the invention
 - Cross References to Related Applications
 - Statement Regarding Fed sponsored R & D
 - Reference to Microfiche Appendix
 - Background of the Invention
 - Brief Summary of the Invention
 - Brief Description of the Drawings (if filed)
 - Detailed Description
 - Claim(s)
 - Abstract of the Disclosure
6. ☐ Microfiche Computer Program (Appendix)
7. Nucleotide and/or Amino Acid Sequence Submission (if applicable, all necessary)
- a. ☐ Computer Readable Copy
 - b. ☐ Paper Copy (identical to computer copy)
 - c. ☐ Statement verifying identity of above copies

3. ☒ Drawing(s) (35 U.S.C. 113) [Total Sheets 12]
4. ☒ Oath or Declaration [Total Pages 2]
- a. ☒ Newly executed (original or copy)
- b. ☐ Copy from a prior application (37 CFR 1.63(d)) *(for continuation/divisional with Box 17 completed)*
[Note Box 5 below]
- i. ☐ **DELETION OF INVENTOR(S)**
Signed statement attached deleting inventor(s) named in the prior application, see 37 CFR §§ 1.63(d)(2) and 1.33(b).
5. ☐ Incorporation By Reference *(useable if Box 4b is checked)*
The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied under Box 4b, is considered as being part of the disclosure of the accompanying application and is hereby incorporated by reference therein

ACCOMPANYING APPLICATION PARTS	
8 <input type="checkbox"/>	Assignment Papers (cover sheet & document(s))
9. <input type="checkbox"/>	37 CFR 3.73(b) Statement (when there is an assignee) <input type="checkbox"/> Power of Attorney
10. <input type="checkbox"/>	English Translation Document (if applicable)
11. <input type="checkbox"/>	Information Disclosure Statement (IDS)/PTO-1449 <input type="checkbox"/> Copies of IDS Citations
12. <input type="checkbox"/>	Preliminary Amendment
13. <input checked="" type="checkbox"/>	Three (3) Return Receipt Postcard (MPEP 503) (Should be specifically itemized)
14. <input type="checkbox"/>	*Small Entity Statement(s) <input type="checkbox"/> Statement filed in prior application, Status still proper and desired
15. <input type="checkbox"/>	Certified Copy of Priority Document(s) (if foreign priority is claimed)
16. <input checked="" type="checkbox"/>	Other. 37 CFR § 1.136(a)(3) Authorization
<input type="checkbox"/> Other	
<small>*NOTE FOR ITEMS 1 & 14. IN ORDER TO BE ENTITLED TO PAY SMALL ENTITY FEES, A SMALL ENTITY STATEMENT IS REQUIRED (37 CFR § 1.17), EXCEPT IF ONE FILED IN A PRIOR APPLICATION IS RELIED UPON (37 CFR § 1.24).</small>	

17. If a CONTINUING APPLICATION, check appropriate box, and supply the requisite information below and in a preliminary amendment.

☐ Continuation ☐ Divisional ☐ Continuation-in-Part (CIP) of prior application No: ____/____

Prior application information: Examiner _____ Group/Art Unit: _____

18. CORRESPONDENCE ADDRESS					
<input type="checkbox"/> Customer Number or Bar Code Label _____ or <input checked="" type="checkbox"/> Correspondence address below					
NAME	STERNE, KESSLER, GOLDSTEIN & FOX P L L C				
ADDRESS	Attorneys at Law				
CITY	Washington	STATE	DC	ZIP CODE	20005-3934
COUNTRY	USA	TELEPHONE	(202) 371-2600	FAX	(202) 371-2540

NAME (Print/Type)	Michael V. Messinger	Registration No. (Attorney/Agent)	37,575
SIGNATURE		Date	7/31/98

Burden Hour Statement: This form is estimated to take 02 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.

STERNE, KESSLER, GOLDSTEIN & FOX P.L.L.C.

ATTORNEYS AT LAW

1100 NEW YORK AVENUE, N.W., SUITE 600

WASHINGTON, D.C. 20005-3934

www.skgf.com

PHONE: (202) 371-2600

FACSIMILE: (202) 371-2540

JC873 U.S. PTO
09/629458
07/31/00

ROBERT GREENE STERNE
EDWARD J. KESSLER
JORGE A. GOLDSTEIN
SAMUEL L. FOX
DAVID K.S. CORNWELL
ROBERT W. ESMOND
TRACY-GENE G. DURKIN
MICHELE A. CIMBALA
MICHAEL B. RAY
ROBERT E. SOKOHL
ERIC K. STEFFE
MICHAEL G. LEE

STEVEN R. LUDWIG
JOHN M. COVERT*
LINDA E. ALCORN
RAZ E. FLESHNER
ROBERT C. MILLONIG
MICHAEL V. MESSINGER
JUDITH U. KIM
TIMOTHY J. SHEA, JR.
DONALD R. MCPHAIL
PATRICK E. GARRETT
STEPHEN G. WHITESIDE
JEFFREY T. HELVEY*

HEIDI L. KRAUS
JEFFREY R. KURIN
RAYMOND MILLIEN
PATRICK D. O'BRIEN
LAWRENCE B. BUGANSKY
CRYSTAL D. SAYLES*
EDWARD W. YEE
ALBERT L. FERRO*
DONALD R. BANOWIT
PETER A. JACKMAN
MOLLY A. MCCALL
TERESA U. MEDLER

JEFFREY S. WEAVER
KRISTIN K. VIDOVICH
KENDRICK P. PATTERSON
DONALD J. FEATHERSTONE
GRANT E. REED
VINCENT L. CAPUANO
JOHN A. HARROUN*
MATTHEW M. CATLETT*
NATHAN K. KELLEY*
ALBERT J. FASULO II*
W. BRIAN EDGE*

KAREN R. MARKOWICZ**
SUZANNE E. ZISKA**
BRIAN J. DEL BUONO**
ANDREA J. KAMAGE**
NANCY J. LEITH**
TARJA H. NAUKKARINEN**

*BAR OTHER THAN D.C.
**REGISTERED PATENT AGENTS

July 31, 2000

WRITER'S DIRECT NUMBER:
(202) 371-2667

INTERNET ADDRESS:
MIKEM@SKGF.COM

Commissioner for Patents
Washington, D.C. 20231

Box Patent Application

Re: U.S. Non-Provisional Utility Patent Application under 37 C.F.R. § 1.53(b)
Appl. No. To Be Assigned; Filed: Herewith
For: **System, Method, and Computer Program Product for Remote
Graphics Processing**
Inventor: Phillip C. KESLIN
Our Ref: 15-4-1034.00

Sir:

The following documents are forwarded herewith for appropriate action by the U.S.
Patent and Trademark Office:

1. PTO Fee Transmittal (Form PTO/SB/17) (*in duplicate*);
2. PTO Utility Patent Application Transmittal (Form PTO/SB/05);
3. U.S. Utility Patent Application entitled:

**System, Method, and Computer Program Product for Remote Graphics
Processing**

Commissioner for Patents

July 31, 2000

Page 2

and naming as inventor:

Phillip C. Keslin

the application consisting of:

- a. A specification containing:
 - i. 16 pages of description prior to the claims;
 - ii. 7 pages of claims (21 claims);
 - iii. a one (1) page abstract;
- b. 12 sheets of drawings: (Figures 1-12); and
- c. An original executed Declaration;
4. Authorization to Treat a Reply As Incorporating An Extension of Time Under 37 C.F.R. § 1.136(a)(3) (*in duplicate*);
5. Recordation Form Cover Sheet;
6. An original executed Assignment to Silicon Graphics, Inc., recordation of which is hereby respectfully requested;
7. Three (3) return postcards; and
8. Our check No. 28243 for \$748.00 to cover:
 - \$ 690.00 Filing fee for patent application;
 - \$ 40.00 Assignment recordation fee; and
 - \$ 18.00 Fee for excess claims.

It is respectfully requested that, of the three attached postcards, one be stamped with the filing date of these documents and returned to our courier, and the other prepaid postcards, be stamped with the filing date and unofficial application number and returned as soon as possible.

001220.9546260

Commissioner for Patents

July 31, 2000

Page 3

The U.S. Patent and Trademark Office is hereby authorized to charge any fee deficiency, or credit any overpayment, to our Deposit Account No. 19-0036. A duplicate copy of this letter is enclosed.

Respectfully submitted,

STERNE, KESSLER, GOLDSTEIN & FOX P.L.L.C.

STERNE, KESSLER, GOLDSTEIN & CO.

Michael V. Messinger
Attorney for Applicant
Registration No. 37,575

MVM/EWY/dnk

Enclosures

P:\USERS\DKELSEY\Attny Documents\EWY\1452\3020000\anonprovapp.ptoltr
SKGF Rev, 5/30/00 mac

System, Method, and Computer Program Product for Remote Graphics Processing

Inventor: Phillip C. Keslin

Background of the Invention

5 ***Field of the Invention***

The present invention relates to computer graphics, and more particularly to graphics computing architecture.

Related Art

10 Today a user of a graphics processing host, such as an INFINITE REALITY system by Silicon Graphics, Inc. of Mountain View, California, runs a graphics application locally. Rendering in response to the graphics instructions is also performed locally. The distance from the host to a user can be extended to a distance of, for example, one to three kilometers by the use of fiberoptic cables to connect the user's monitor and keyboard with the graphics processing
15 host. More important, the host is the dedicated resource of a single person. It can only be shared if someone else takes the place of the current user. While a dedicated resource is convenient for the user, it may not be economical. The cost of a graphics processing host is considerable; less than full usage of such a host lowers its cost-effectiveness. This lower cost-effectiveness could deter an
20 organization from procuring a graphics processing host.

Hence there is a need for a system and method by which additional users can utilize a remote graphics processing host. This would improve the cost-effectiveness of the host. Specifically, a system and method are needed where a user can execute a graphics application at a remote graphics processing host,

causing rendering to be performed at the host such that the resulting images are returned to the user.

Summary of the Invention

5 The invention described herein is a system, method, and computer program product for remote rendering of computer graphics. The invention includes a graphics application program resident at a remote server. The graphics application is invoked by a user or process located at a client. At the server, the invoked graphics application proceeds to issue graphics instructions. The graphics instructions are received by a remote rendering control system. Given that the client and server differ with respect to graphics context and image processing capability, the remote rendering control system modifies the graphics instructions in order to accommodate these differences. The modified graphics instructions are sent to graphics rendering resources, which produce one or more rendered images. Data representing the rendered images is written to one or more frame buffers. 10 The remote rendering control system then reads this image data from the frame buffers. The image data is transmitted to the client for display or processing. In an embodiment of the invention, the image data is compressed before being transmitted to the client. In such an embodiment, the steps of rendering, compression, and transmission can be performed asynchronously in a pipelined manner. 15 20

Features and Advantages

25 The invention described herein has the feature of allowing a user to invoke a graphics application at a remote server. The invention also has the feature of allowing the graphics application to send graphics instructions to graphics rendering resources located with the server, so that rendering is performed at the

host and not at the user's machine. The invention also has the feature of returning rendered image data to the user.

The invention has the advantage of allowing a user to utilize graphics resources that are not co-located with the user, but are instead located at a distance from the user. The invention also has the advantage of allowing greater utilization of graphics resources, since users other than local users can take advantage of graphics resources.

The foregoing and other features and advantages of the invention will be apparent from the following, more particular description of a preferred embodiment of the invention, as illustrated in the accompanying drawings.

Brief Description of the Figures

FIG. 1 illustrates the overall architecture of an embodiment of the invention.

FIG. 2 is a block diagram of the remote rendering control system, according to an embodiment of the invention.

FIG. 3 is a flowchart illustrating the method of the invention, according to an embodiment thereof.

FIG. 4 is a flowchart illustrating the step of initialization, according to an embodiment of the invention.

FIG. 5 is a flowchart illustrating the client / server handshake, according to an embodiment of the invention.

FIG. 6 is a flowchart illustrating the graphics application's receipt of a client window, according to an embodiment of the invention.

FIG. 7 is a flowchart illustrating the graphics application's receipt of a graphics context, according to an embodiment of the invention.

FIG. 8 is a flowchart illustrating the binding of a server context to a server window, according to an embodiment of the invention.

FIG. 9 is a flowchart illustrating the step of imposing client parameters on the rendering process, according to an embodiment of the invention.

FIG. 10 illustrates the pipelining of the rendering, compression, and transmission operations, according to an embodiment of the invention.

FIG. 11 is a flowchart illustrating the remote rendering process from the perspective of the client, according to an embodiment of the invention.

FIG. 12 illustrates the computing environment of the invention, according to an embodiment thereof.

Detailed Description of the Preferred Embodiments

A preferred embodiment of the present invention is now described with reference to the figures where like reference numbers indicate identical or functionally similar elements. Also in the figures, the left most digit of each reference number corresponds to the figure in which the reference number is first used. While specific configurations and arrangements are discussed, it should be understood that this is done for illustrative purposes only. A person skilled in the relevant art will recognize that other configurations and arrangements can be used without departing from the spirit and scope of the invention. It will be apparent to a person skilled in the relevant art that this invention can also be employed in a variety of other systems and applications.

Contents

I. Introduction

II. Apparatus

III. Method

A. Server processing

1. Initialization

a. Client/server handshake

- b. Client window
- c. Graphics context
- d. Context and server window

2. Client parameters

5 3. Rendering and transmission

B. Client processing

IV. Environment

V. Conclusion

I. Introduction

10 The invention described herein is a system, method, and computer program
product for remote rendering of computer graphics. The invention allows a user
or process at a client computer to access remotely located rendering resources,
such as a graphics processing host embodied in or co-located with a remotely
15 located server. According to the invention, a graphics application executing at the
server sends graphics instructions to a remote rendering control system. The
remote rendering control system can be embodied in software running on the
server. The instructions sent from the application are not sent to the client. Hence
the client does no rendering. The instructions are modified by the remote
rendering control system and sent to graphics rendering resources. Rendering
20 consequently takes place at the graphics resources. The image data that is
produced by the graphics resources are then sent to the client.

II. Apparatus

25 The basic architecture of an embodiment of the present invention is
illustrated in FIG. 1. A user or process at a client machine 103 wishes to have
rendering performed remotely. Accordingly, client 103 issues commands 107 to

09029458.073100

a remotely located server 109. In an embodiment of the invention, connectivity between client 103 and server 109 is established and maintained through a communications network 115, such as the internet. Commands 107 are received at server 109 by a graphics application 120. In response to commands 107,
5 application 120 generates graphics instructions 125. Graphics instructions may, for example, be in the OPENGL language.

Graphics instructions 125 are sent to a remote rendering control system 130. Remote rendering control system 130 accepts graphics instructions 125 and modifies them to create modified graphics instructions 135. An example of a
10 remote rendering control system is the VIZSERVER software system produced by Silicon Graphics, Inc. As will be described in greater detail below, the modifications to graphics instructions 125 are performed to take into account the differences between server 109 and client 103 with respect to their imaging processing capabilities and graphics contexts. In response to modified graphics
15 instructions 135, graphics resources 140 render one or more images and return image data 145 to remote rendering control system 130. In an embodiment of the invention, image data 145 is then compressed to form compressed image data 150. Compressed image data 150 is then sent to client 103, via network 115. In alternative embodiments of the invention, compression is not implemented.

20 A more detailed logical illustration of remote rendering control system 130 is shown in FIG. 2. Remote rendering control system 130 accepts graphics instructions 125 through an interface 205 which is transparent to the graphics application 120. Graphics application 120 is effectively sending graphics instructions to local rendering resources instead of to client 103. Because of the
25 transparency of interface 205, graphics application 120 need not be aware of this redirection. Transparent interface 205 performs a variety of modifications to graphics instructions 125, to produce modified graphics instructions 135. The modifications performed by transparent interface 205 will be described in greater detail below. Modified graphics instructions 135 are then sent to graphics
30 resources 140 (not shown in FIG. 2) to effect rendering.

After rendering has been performed, remote rendering control system 130 accepts the resulting image data 145. As described above, in an embodiment of the invention, image data 145 undergoes compression before transmission to client 103. Compression of the data is performed by a data compression module 210, which produces compressed image data 150. Various methods of data compression are known to persons of ordinary skill in the art. In an embodiment of the invention, color cell compression is used. In alternative embodiments of the invention, data compression module 210 can perform alternative compression algorithms, such as the process described in U.S. Patent Application 09/458,011, "Image Data Compression and Decompression," incorporated herein by reference in its entirety. In an embodiment of the invention, data compression module 210 is capable of performing any of a plurality of data compression algorithms.

III. Method

The overall process of an embodiment of the invention is illustrated in FIG. 3. Process 300 starts at step 305. At step 310, a graphics session between a client and a remote server is initialized. Initialization step 310 includes the client's initial access to and protocol "handshake" with the server. In addition, step 310 includes the starting of the graphics application. Step 310 also includes reconciling the differences between the client and server with respect to graphics processing capability and graphics context. Such reconciliation is necessary to allow processing of an image at the server and display (or further processing) of the image at the client. Initialization will be described in greater detail below.

In step 320, the graphics application generates graphics instructions for the remote rendering control system. In step 325, parameters specific to the client are imposed. This step includes, for example, interception by the transparent interface of function calls and references that occur in the graphics instructions, and the modification of those function calls and references to make them suitable to the client. In particular, adjustments may have to be made given that the client and

server can have different graphics processing capabilities and contexts. Step 325 is described in greater detail below.

In step 330, the remote rendering control system sends modified graphics instructions to the graphics resources. The modified instructions of this step correspond to the graphics instructions generated in step 320 and modified in step 325. In step 335, the graphics resources render one or more images according to the modified instructions of step 330.

In step 340, after rendering is completed, the remote rendering control system reads the resulting image data from a frame buffer. In an embodiment of the invention, the graphics application can have one or more specific instructions that force the reading of the frame buffer. If, for example, OPENGGL is being used, the instruction "glFlush" causes the frame buffer to be "flushed," i.e., read. The OPENGGL instruction "glSwapBuffers" also serves this purpose where two frame buffers are used. Here, the buffers will be swapped. A first buffer, to which image data has most recently been written, will be read. Writing, meanwhile, now takes place into the second buffer. Likewise, at the next "glSwapBuffers" instruction, the second buffer will be read and the first buffer will begin receiving new image data.

In step 345, the image data is enqueued for purposes of compression. In step 350, the image data is compressed so that in step 355 the image data can be transmitted to the client efficiently. In step 360, a determination is made as to whether additional rendering is necessary. If so, the process returns to step 320. If no additional rendering is required in step 360, the process concludes at step 365.

A. Server processing

1. Initialization

006629458-073100

The initialization step 310, according to an embodiment of the invention, is illustrated in greater detail in FIG. 4. The process begins at step 405. In step 410, a user or process at the client machine, begins logging on to the server. As a result, in step 415 a client/server handshake takes place. The handshake includes the initial contact and protocol establishment between the server and client. Step 415 also includes an agreement process between the client and server as to which data compression algorithm will be used, if there are more than one available. The client/server handshake process is described in greater detail below with respect to FIG. 5. In step 420, the client exports to the server a list of the client's graphics capabilities. A list of specific graphics capabilities is known as a visual. Examples of capabilities that may be included in a visual are the ability to perform stenciling or represent opacity. Another component of a visual is the color mapping range of a device, e.g., 48-bit versus 24-bit color representation.

In step 425, the user or process starts a console window at the client computer. In step 430, the user or process starts the graphics application resident at the server. In step 435, the transparent interface to the graphics application opens the client display and the server display. In step 440, the transparent interface merges the visual of the client with the visual of the server. Because a graphics application typically deals with a single output device, the graphics application must see a single visual. This merger allows the graphics application to see a single visual, while in reality presenting visuals for both client and server. In step 445, the transparent interface associates the client display with the graphics application. In step 450, the transparent interface overlays the server visual with a routine that allows conversion of visual capabilities appearing in function calls of the graphics application. The routine converts these visual capabilities to capabilities appropriate to the client, i.e., capabilities in the client's original visual. The development and application of such a routine would be obvious to one of ordinary skill in the art given this description.

In step 455, the client window is returned to the graphics application. This step includes the conversion, by the transparent interface, of the merged visual list

into a visual appropriate to the client. Step 455 also includes creation of an internal data structure for tracking the position of the client window in the client display. The process of receiving the client window is described in greater detail below with respect to FIG. 6.

5 In step 460, the application receives a graphics context. This step, detailed below with respect to FIG. 7, includes definition of a server context by the transparent interface. Step 460 also includes the return of an internal context to the application. In step 465, the application binds the internal context to the client window, which has the effect of binding the server context to the server window. 10 The initialization process concludes with step 470.

a. Client / server handshake

An embodiment of the client/server handshake, step 415, is illustrated in greater detail in FIG. 5. This process begins with step 505. In step 510, the server connects to the client. In step 515, the server (in particular, the application) 15 identifies an address or source from which updates of image data are provided. It is from this source that updates will be sent to the client. In step 520, the server and client identify their respective available compression algorithms to each other. In step 525, the client chooses a compression algorithm and identifies it to the server. The process concludes with step 530.

b. Client window

20 The step by which a client window is returned to the application, step 455, is illustrated in greater detail in FIG. 6, according to an embodiment of the invention. The process begins with step 605. In step 610, the transparent interface produces a visual appropriate for the client from the merged visual list. 25 This is done by taking only those visual capabilities which were originally the client's. Definition of such a visual is required for an image to be displayed

properly at the client. In step 615, the transparent interface defines a window for the client. In step 620, the transparent interface creates an internal data structure for tracking the position of the client window on the client display. In step 625, the transparent interface returns the client window to the application. The process concludes with step 630.

c. Graphics context

An embodiment of the process by which a graphics context is returned to the application, step 460, is illustrated in greater detail in FIG. 7. The process begins with step 705. In step 710, the transparent interface produces a server visual from the merged visual. This is done by taking only those visual capabilities which were originally the server's. In step 715, the transparent interface defines a server context. The server context represents the context settings to be applied in rendering for the server's display. In step 720, the transparent interface returns an internal context to the application program, where the internal context includes the server context and any additional information that may be necessary to allow the transparent interface to properly interpret references to the server context. An example of such additional information is the identity of specific visual capabilities that correspond to a given element of the server context. The process concludes with step 725.

d. Context and server window

The step of binding a context to a server window, step 465, is illustrated in greater detail in FIG. 8, according to an embodiment of the invention. The process begins with step 805. In step 810, the transparent interface extracts the server context from the internal context. In step 815, the transparent interface requests a window allocation from the session manager. The session manager is logic (e.g., software) responsible for managing the allocation of resources in a

graphics session. The implementation of a session manager is known to persons of ordinary skill in the art. In step 820, the transparent interface binds the server context to the server window. The process concludes with step 825.

2. Client parameters

Returning to the overall process 300 illustrated in FIG. 3, once initialization is completed in step 310, the graphics application generates graphics instructions in step 320, as discussed above. This is followed by step 325, the step of imposing client parameters on the rendering process. An embodiment of step 325 is illustrated in greater detail in FIG. 9. The process begins with step 905. In step 910, the transparent interface intercepts graphics instruction function calls that include a visual. In step 915, the transparent interface converts the visuals to corresponding client visuals. In step 920, the transparent interface intercepts every graphics instruction reference to a context. In step 925 the transparent interface converts the reference to a reference consistent with the client's context. The process concludes at step 930.

3. Rendering and transmission

Steps 340 through 355 (rendering, enqueueing, compression, and transmission) are collectively illustrated in FIG. 10, according to an embodiment of the invention. This figure illustrates how blocks of image data are rendered, compressed, then transmitted. In the illustrated embodiment, these operations are performed in pipeline fashion. The rendering, compression, and transmission steps are identified collectively as processes 1005. These steps take place sequentially during successive blocks of time 1010. During time t_0 , a block A of image data is rendered. During the next interval, time t_1 , block A is compressed. Simultaneously, the next segment of image data, block B, is rendered. At the next time interval, t_2 , block A is transmitted after having been compressed during the

previous time period. While block A is being transmitted, block B is compressed. Simultaneously, the next block of image data, block C, is being rendered. Successive blocks of image data are processed in this manner.

5 In an embodiment of the invention, the steps of rendering, compression, and transmission are asynchronous. In such an embodiment, the compression of block B may not be completed at the same time as the rendering of block C, referring to the example above. To deal with this, blocks of image data may be discarded. Any given step will take only the most recent block from the previous step. If, for example, rendering of block B takes place faster than the compression of block A, the compression module is not yet ready for block B when rendering of block B is done. Block B will therefore be discarded. The compression module will finish compressing block A, then wait for the next (and newest) block to emerge from rendering. Multiple blocks may be discarded if rendering is significantly faster than compression. The transmission process will likewise accept only the newest compressed block of image data. If compression of a block is completed before the previous block has been transmitted, that compressed block will be discarded.

B. Client processing

20 An embodiment of the remote rendering process from the perspective of the client is illustrated in FIG. 11. The process starts with step 1105. In step 1110, the client/server handshake takes place, as described above. In step 1115, the client sends one or more commands to the graphics application to begin execution. In step 1120, after the graphics resources at the server have completed rendering, the client receives image data via the network. In an embodiment of the invention, the image data is compressed for purposes of transmission efficiency. In step 1125, the image data is decompressed at the client and in step 1130, the appropriate image is drawn to a window at the client. In step 1135 a

determination is made as to whether an additional image is to be drawn. If so, the process continues at step 1120. Otherwise the process concludes at step 1140.

IV. Environment

Server 109 of the present invention may be implemented as a computer system or other processing system. Remote rendering control system 130 and graphics application program 120 can be implemented as computer programs executing on such a computer system. Graphics resources 140 can be any type of graphics subsystem linked to a communication infrastructure 1206, such as a bus or network. An example of such a computer system 1200 is shown in FIG. 12. The computer system 1200 includes one or more processors, such as processor 1204. The processor 1204 is connected to communication infrastructure 1206. Various software implementations are described in terms of this exemplary computer system. After reading this description, it will become apparent to a person skilled in the relevant art how to implement the invention using other computer systems and/or computer architectures.

Computer system 1200 also includes a main memory 1208, preferably random access memory (RAM), and may also include a secondary memory 1210. The secondary memory 1210 may include, for example, a hard disk drive 1212 and/or a removable storage drive 1214, representing a floppy disk drive, a magnetic tape drive, an optical disk drive, etc. The removable storage drive 1214 reads from and/or writes to a removable storage unit 1218 in a well known manner. Removable storage unit 1218, represents a floppy disk, magnetic tape, optical disk, or other storage medium which is read by and written to by removable storage drive 1214. As will be appreciated, the removable storage unit 1218 includes a computer usable storage medium having stored therein computer software and/or data.

In alternative implementations, secondary memory 1210 may include other means for allowing computer programs or other instructions to be loaded into

computer system 1200. Such means may include, for example, a removable storage unit 1222 and an interface 1220. Examples of such means may include a program cartridge and cartridge interface (such as that found in video game devices), a removable memory chip (such as an EPROM, or PROM) and associated socket, and other removable storage units 1222 and interfaces 1220 which allow software and data to be transferred from the removable storage unit 1222 to computer system 1200.

Computer system 1200 may also include a communications interface 1224. Communications interface 1224 allows software and data to be transferred between computer system 1200 and external devices. Examples of communications interface 1224 may include a modem, a network interface (such as an Ethernet card), a communications port, a PCMCIA slot and card, etc. Software and data transferred via communications interface 1224 are in the form of signals 1228 which may be electronic, electromagnetic, optical or other signals capable of being received by communications interface 1224. Commands 107 and compressed image data 150 are examples of signals 1228. These signals 1228 are provided to communications interface 1224 via a communications path (i.e., channel) 1226. This channel 1226 carries signals 1228 and may be implemented using wire or cable, fiber optics, a phone line, a cellular phone link, an RF link and other communications channels.

In this document, the terms "computer program medium" and "computer usable medium" are used to generally refer to media such as removable storage units 1218 and 1222, a hard disk installed in hard disk drive 1212, and signals 1228. These computer program products are means for providing software to computer system 1200.

Computer programs (also called computer control logic) are stored in main memory 1208 and/or secondary memory 1210. Computer programs may also be received via communications interface 1224. Remote rendering control system 130 and graphics application program 120 can be implemented as computer programs. Such computer programs, when executed, enable the computer system

1200 to implement the present invention as discussed herein. In particular, the computer programs, when executed, enable the processor 1204 to implement the present invention. Accordingly, such computer programs represent controllers of the computer system 1200. Where the invention is implemented using software, the software may be stored in a computer program product and loaded into computer system 1200 using removable storage drive 1214, hard drive 1212 or communications interface 1224.

V. Conclusion

While various embodiments of the present invention have been described above, it should be understood that they have been presented by way of example, and not limitation. It will be apparent to persons skilled in the relevant art that various changes in detail can be made therein without departing from the spirit and scope of the invention. Thus the present invention should not be limited by any of the above-described exemplary embodiments, but should be defined only in accordance with the following claims and their equivalents.

What Is Claimed Is:

1 1. A system for providing a client with access to remote graphics
2 rendering resources, comprising:

3 a remote rendering control system that receives graphics
4 instructions, generates modified graphics instructions on the basis of said graphics
5 instructions, and outputs said modified graphics instructions to said graphics
6 rendering resources.

1 2. The system of claim 1, wherein said remote rendering control
2 system comprises a transparent interface to said graphics application, and wherein
3 said transparent interface supports initialization of a graphics rendering session and
4 accommodates client parameters during said graphics rendering session.

1 3. The system of claim 1, wherein said remote rendering control
2 system comprises a data compression module that compresses said image data
3 prior to sending said image data to said client.

1 4. The system of claim 1, wherein said remote rendering control
2 system receives image data generated by said graphics rendering resources on the
3 basis of said modified graphics instructions, and sends said image data to said
4 client.

1 5. The system of claim 1, wherein said remote rendering control
2 system receives graphics instructions from a graphics application program.

1 6. A method of remote graphics rendering on behalf of a client,
2 comprising the steps of:

3 (A) initializing a graphics rendering session;

4 (B) starting a graphics application on the basis of a command
5 from the client;

6 (C) generating graphics instructions;

7 (D) imposing client parameters to produce modified graphics
8 instructions;

9 (E) sending the modified graphics instructions to graphics
10 rendering resources;

(F) rendering graphics on the basis of the modified graphics instructions to produce image data in one or more frame buffers;

13 (G) reading image data from the one or more frame buffers;

4 (H) enqueueing the image data; and

5 (I) transmitting the image data to the client.

1 7. The method of claim 6, further comprising the step of:

(J) compressing the image data,
performed after step (H) and before step (I).

1 8. The method of claim 7, wherein steps (F), (J), and (I) are
2 performed in pipeline fashion.

1 9. The method of claim 8, wherein steps (F), (J), and (I) are
2 asynchronous.

1 10. The method of claim 6, wherein step (A) comprises the steps of:

2 (i) performing a client / server handshake:

3 (ii) receiving a client visual from the client;

4 (iii) after a user at the client opens a console window at the
5 client and starts the graphics application, opening client and server displays;

(iv) merging the client visual with a server visual to form a merged visual list;

- (v) associating the client display with the graphics application;
- (vi) overlaying the server visual list with a transparent interface routine;
- (vii) enabling the return of a client window to the graphics application;
- (viii) enabling the return of an internal context to the graphics application; and
- (ix) binding a server context to the server window.

11. The method of claim 10, wherein step (vii) comprises the steps of:

- (a) converting the merged visual list into a visual appropriate for the client;
- (b) defining the client window;
- (c) creating an internal data structure for tracking the displayed location of the client window; and
- (d) returning the client window to the graphics application.

12. The method of claim 10, wherein step (viii) comprises the steps of:

- (e) converting the merged visual list into a visual appropriate for the server;
- (f) creating a server context; and
- (g) returning an internal context to the application.

13. The method of claim 10, wherein step (ix) comprises the steps of:

- (h) extracting a server context from the internal context;
- (i) requesting a window allocation from a session manager; and
- (j) associating the server context with a server window.

1 14. The method of claim 6, wherein step (D) comprises the steps of:
2 (x) intercepting every function call that includes a visual
3 capability;
4 (xi) converting the visual capability to a corresponding client
5 visual capability;
6 (xii) intercepting every reference to a graphics context; and
7 (xiii) converting every reference to a graphics context to a
8 reference to a graphics context of the client.

1 15. A computer program product comprising a computer usable
2 medium having computer readable program code that enables remote graphics
3 rendering on behalf of a client, said computer readable program code comprising:
4 first computer readable program code logic for causing a server to
5 initialize a graphics rendering session;
6 second computer readable program code logic for causing the
7 server to start a graphics application on the basis of a command from the client;
8 third computer readable program code logic for causing the server
9 to generate graphics instructions;
10 fourth computer readable program code logic for causing the
11 server to impose client parameters to produce modified graphics instructions;
12 fifth computer readable program code logic for causing the server
13 to send the modified graphics instructions to graphics rendering resources;
14 sixth computer readable program code logic for causing the
15 graphics rendering resources to render graphics on the basis of the modified
16 graphics instructions to produce image data in one or more frame buffers;
17 seventh computer readable program code logic for causing the
18 server to read image data from the one or more frame buffers;
19 eighth computer readable program code logic for causing the
20 server to enqueue the image data; and

ninth computer readable program code logic for causing the server to transmit the image data to the client.

16. The computer program product of claim 15, said computer readable program code further comprising:

tenth computer readable program code logic for causing the server to compress the image data.

17. The computer program product of claim 15, wherein said first computer readable program code logic comprises:

(i) computer readable program code logic for causing the server to participate in a client / server handshake;

(ii) computer readable program code logic for causing the server to receive a client visual from the client;

(iii) computer readable program code logic for causing the server to open client and server displays after a user at the client opens a console window at the client and starts the graphics application;

(iv) computer readable program code logic for causing the server to merge the client visual with a server visual to form a merged visual list;

(v) computer readable program code logic for causing the server to associate the client display with the graphics application;

(vi) computer readable program code logic for causing the server to overlay the server visual list with a transparent interface routine;

(vii) computer readable program code logic for causing the server to enable the return of a client window to the graphics application;

(viii) computer readable program code logic for causing the server to enable the return of an internal context to the graphics application; and

(ix) computer readable program code logic for causing the server to bind a server context to the server window.

1 18. The computer program product of claim 17, wherein said computer
2 readable program code logic (vii) comprises:

3 (a) computer readable program code logic for causing the
4 server to convert the merged visual list into a visual appropriate for the client;

5 (b) computer readable program code logic for causing the server
6 to define the client window;

7 (c) computer readable program code logic for causing the server
8 to create an internal data structure for tracking the displayed location of the client
9 window; and

10 (d) computer readable program code logic for causing the server
11 to return the client window to the graphics application.

1 19. The computer program product of claim 17, wherein said computer
2 readable program code logic (viii) comprises:

3 (a) computer readable program code logic for causing the
4 server to convert the merged visual list into a visual appropriate for the server;

5 (b) computer readable program code logic for causing the
6 server to create a server context; and

7 (c) computer readable program code logic for causing the
8 server to return an internal context to the application.

1 20. The computer program product of claim 17, wherein said computer
2 readable program code logic (ix) comprises:

3 (a) computer readable program code logic for causing the server
4 to extract a server context from the internal context;

5 (b) computer readable program code logic for causing the server
6 to request a window allocation from a session manager; and

7 (c) computer readable program code logic for causing the server
8 to associate the server context with a server window.

1 21. The computer program product of claim 15, wherein said fourth
2 computer readable program code logic comprises:

3 (i) computer readable program code logic for causing the
4 server to intercept every function call that includes a visual capability;

5 (ii) computer readable program code logic for causing the
6 server to convert the visual capability to a corresponding client visual capability;

7 (iii) computer readable program code logic for causing the
8 server to intercept every reference to a graphics context; and

9 (iv) computer readable program code logic for causing the
10 server to convert every reference to a graphics context to a reference to a graphics
11 context of the client.

09529458-073100

System, Method, and Computer Program Product for Remote Graphics Processing

Abstract

5 A system, method, and computer program product are provided for remote rendering of computer graphics. The system includes a graphics application program resident at a remote server. The graphics application is invoked by a user or process located at a client. The invoked graphics application proceeds to issue graphics instructions. The graphics instructions are received by a remote rendering control system. Given that the client and server differ with respect to graphics context and image processing capability, the remote rendering control system modifies the graphics instructions in order to accommodate these differences. The modified graphics instructions are sent to graphics rendering resources, which produce one or more rendered images. Data representing the rendered images is written to one or more frame buffers. The remote rendering control system then reads this image data from the frame buffers. The image data is transmitted to the client for display or processing. In an embodiment of the system, the image data is compressed before being transmitted to the client. In such an embodiment, the steps of rendering, compression, and transmission can be performed asynchronously in a pipelined manner.

20 P:\USERS\EYEE\SGI1452\1452.302\A276-57.wpd

0002-28 vsd1




FIG. 1

001E20-85762960




FIG. 2




FIG. 3






FIG. 4

**FIG. 5**

**FIG. 6**

000228.vsd 07/31/00




FIG. 7





FIG. 8

**FIG. 9**

0002-28.vsd11

Time
1010



t_0

t_1

t_2

	Render	Compress	Transmit
t_0	A		
t_1	B	A	
t_2	C	B	A

Processes 1005 →

1000



FIG. 10




FIG. 11




FIG. 12

Declaration for Patent Application

Docket Number: 15-4-1034.00

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter that is claimed and for which a patent is sought on the invention entitled System, Method, and Computer Program Product for Remote Graphics Processing, the specification of which is attached hereto unless the following box is checked:

- ☐ was filed on _____;
as United States Application Number or PCT International Application Number _____; and
was amended on _____ (if applicable).

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information that is material to patentability as defined in 37 C.F.R. § 1.56.

I hereby claim foreign priority benefits under 35 U.S.C. § 119(a)-(d) or § 365(b) of any foreign application(s) for patent or inventor's certificate, or § 365(a) of any PCT international application, which designated at least one country other than the United States listed below, and have also identified below any foreign application for patent or inventor's certificate, or PCT international application having a filing date before that of the application on which priority is claimed.

Prior Foreign Application(s)	Priority Claimed
_____ (Application No.)	_____ (Country)
_____ (Application No.)	_____ (Country)

☐ Yes ☐ No

☐ Yes ☐ No

I hereby claim the benefit under 35 U.S.C. § 119(e) of any United States provisional application(s) listed below.

_____ (Application No.)	_____ (Filing Date)
_____ (Application No.)	_____ (Filing Date)

I hereby claim the benefit under 35 U.S.C. § 120 of any United States application(s), or under § 365(c) of any PCT international application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT international application in the manner provided by the first paragraph of 35 U.S.C. § 112, I acknowledge the duty to disclose information that is material to patentability as defined in 37 C.F.R. § 1.56 that became available between the filing date of the prior application and the national or PCT international filing date of this application.

_____ (Application No.)	_____ (Filing Date)	_____ (Status - patented, pending, abandoned)
_____ (Application No.)	_____ (Filing Date)	_____ (Status - patented, pending, abandoned)


Send Correspondence to:

STERNE, KESSLER, GOLDSTEIN & FOX P.L.L.C.
1100 New York Avenue, N.W.
Suite 600
Washington, D.C. 20005-3934

Direct Telephone Calls to:

(202) 371-2600

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full name of sole or first inventor	Phillip C Keslin	
Signature of sole or first inventor		Date 7/26/2000
Residence	San Jose, California	
Citizenship	United States	
Post Office Address	7483 Phinney Way, San Jose, California 95139	
Full name of second inventor		
Signature of second inventor		Date
Residence		
Citizenship		
Post Office Address		
Full name of third inventor		
Signature of third inventor		Date
Residence		
Citizenship		
Post Office Address		